

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/29/2022

Reviewed on 09/29/2022

**1 Identification**

- **Product Identifier**
- **Trade Name: Crawford's Vinyl Spackling Paste**
- **Relevant identified uses of the substance or mixture and uses advised against:**
- **Product Description:** No further relevant information available.
- **Details of the Supplier of the Safety Data Sheet:**
- **Manufacturer/Supplier:**  
Crawford Products Co.  
16835 Algonquin St. #499  
Huntington Beach, CA 92649  
Phone: 323-721-6429  
Fax: 323-721-0826
- **Emergency telephone number:** 323-721-6429

**2 Hazard(s) Identification**

- **Classification of the substance or mixture:**



Health hazard

Germ Cell Mutagenicity 1B  
Carcinogenicity 1B

H340 May cause genetic defects.  
H350 May cause cancer.



Skin Irritation 2  
Eye Irritation 2A  
Sensitization - Skin 1  
Specific Target Organ Toxicity - Single Exposure 3

H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.

- **Label elements:**
- **Hazard pictograms:**



- **Signal word:** Danger
- **Hazard-determining components of labeling:**  
Trade Secret
- **Hazard statements:**  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H340 May cause genetic defects.  
H350 May cause cancer.  
H335 May cause respiratory irritation.
- **Precautionary statements:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

(Contd. on page 2)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/29/2022

Reviewed on 09/29/2022

### Trade Name: Crawford's Vinyl Spackling Paste

|                |  |
|----------------|--|
| P264           | Wash thoroughly after handling.  |
| P271           | Use only outdoors or in a well-ventilated area.  |
| P272           | Contaminated work clothing must not be allowed out of the workplace.   |
| P280           | Wear protective gloves/protective clothing/eye protection/face protection.   |
| P302+P352      | If on skin: Wash with plenty of water.   |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |
| P305+P351+P338 | If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308+P313      | IF exposed or concerned: Get medical advice/attention.   |
| P312           | Call a poison center/doctor if you feel unwell.  |
| P321           | Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).   |
| P362+P364      | Take off contaminated clothing and wash it before reuse.   |
| P332+P313      | If skin irritation occurs: Get medical advice/attention.   |
| P333+P313      | If skin irritation or rash occurs: Get medical advice/attention.   |
| P337+P313      | If eye irritation persists: Get medical advice/attention.  |
| P363           | Wash contaminated clothing before reuse.   |
| P403+P233      | Store in a well-ventilated place. Keep container tightly closed.   |
| P405           | Store locked up.   |
| P501           | Dispose of contents/container in accordance with local/regional/national/international regulations.                              |

- **Unknown acute toxicity:**

This value refers to knowledge of known, established toxicological or ecotoxicological values. 69 % of the mixture consists of component(s) of unknown toxicity.

- **Classification system:** NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

|            |   |                     |
|------------|---|---------------------|
| HEALTH     | 2 | Health = *2         |
| FIRE       | 0 | Fire = 0            |
| REACTIVITY | 0 | Physical Hazard = 0 |

- **Hazard(s) not otherwise classified (HNOC):** None known

### 3 Composition/Information on Ingredients

- **Chemical characterization: Substance**

- **Description:** Mixture of substances listed below with non-hazardous additions.

- **Dangerous Components:**

|  |        |
|--|--------|
| Trade Secret   | 60-90% |
| ⚠ Skin Irritation 2, H315; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335 |        |
| Trade Secret   | ≤2.5%  |
| ⚠ Aquatic Acute 1, H400  |        |

(Contd. on page 3)








## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/29/2022

Reviewed on 09/29/2022

### Trade Name: Crawford's Vinyl Spackling Paste

|  |       |
|--|-------|
| Trade Secret<br> Flammable Liquids 3, H226;  Germ Cell Mutagenicity 1B, H340; Carcinogenicity 1B, H350; Aspiration Hazard 1, H304;  Acute Toxicity - Inhalation 4, H332   | ≤2.5% |
| Trade Secret<br> Acute Toxicity - Inhalation 3, H331;  Eye Damage 1, H318;  Aquatic Acute 1, H400;  Acute Toxicity - Oral 4, H302; Skin Irritation 2, H315; Sensitization - Skin 1, H317<br>Specific concentration limit: Sensitization - Skin 1; H317: C ≥ 0.05 % | ≤2.5% |

· **Additional information:**

Trade secret made in accordance with paragraph (i) of §1910.1200 of 29 CFR 1910.1200, the OSHA Hazard Communication Standard and U.S. Code of Federal Regulations.

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

#### 4 First-Aid Measures

· **Description of first aid measures**

· **General information:** If symptoms persist, call a physician.

· **After inhalation:** In case of unconsciousness place patient stably in the side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

· **After eye contact:**

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

If easy to do so, remove contact lenses if worn.

If eye irritation occurs, consult a doctor.

· **After swallowing:** If swallowed and symptoms occur, consult a doctor.

· **Information for doctor**

· **Most important symptoms and effects, both acute and delayed:** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed:**

No further relevant information available.

#### \* 5 Fire-Fighting Measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

Use fire fighting measures that suit the environment.

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** No further relevant information.

· **Special hazards arising from the substance or mixture:** No further relevant information available.

· **Advice for firefighters**

· **Special protective equipment for firefighters:**

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

#### 6 Accidental Release Measures

· **Personal precautions, protective equipment and emergency procedures:** Not required.

· **Environmental precautions:** No special measures required.

· **Methods and material for containment and cleaning up:**

Dispose of contaminated material as waste according to section 13.

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

(Contd. on page 4)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/29/2022

Reviewed on 09/29/2022

### Trade Name: Crawford's Vinyl Spackling Paste

· **Reference to other sections:**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **PAC-1:**

|           |                  |                       |
|-----------|------------------|-----------------------|
| 56-81-5   | Glycerol         | 45 mg/m <sup>3</sup>  |
| 1310-73-2 | Sodium Hydroxide | 0.5 mg/m <sup>3</sup> |

· **PAC-2:**

|           |                  |                       |
|-----------|------------------|-----------------------|
| 56-81-5   | Glycerol         | 180 mg/m <sup>3</sup> |
| 1310-73-2 | Sodium Hydroxide | 5 mg/m <sup>3</sup>   |

· **PAC-3:**

|           |                  |                         |
|-----------|------------------|-------------------------|
| 56-81-5   | Glycerol         | 1,100 mg/m <sup>3</sup> |
| 1310-73-2 | Sodium Hydroxide | 50 mg/m <sup>3</sup>    |

## 7 Handling and Storage

· **Handling**

· **Precautions for safe handling:**

Avoid creating and breathing dust/fume/gas/mist/vapors/spray.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· **Information about protection against explosions and fires:** Keep protective respiratory device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and receptacles:** Store in the original container.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep receptacle tightly sealed.

· **Specific end use(s):** No further relevant information available.

## \* 8 Exposure Controls/Personal Protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters:**

· **Components with occupational exposure limits:**

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

| Trade Secret |   |
|--------------|---|
| NIOSH        | Short-term value: 5 mg/m <sup>3</sup><br>Long-term value: 10 mg/m <sup>3</sup>                        |
| NIOSH TWA    | Short-term value: 5 mg/m <sup>3</sup><br>Long-term value: 10 mg/m <sup>3</sup><br>respirable dust     |
| OSHA         | Short-term value: 5 mg/m <sup>3</sup><br>Long-term value: 15 mg/m <sup>3</sup>                        |
| OSHA TWA     | Short-term value: 5 mg/m <sup>3</sup><br>Long-term value: 15 mg/m <sup>3</sup><br>respirable fraction |

(Contd. on page 5)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/29/2022

Reviewed on 09/29/2022

### Trade Name: Crawford's Vinyl Spackling Paste

- **Additional information:** The lists that were valid during the creation of this SDS were used as basis.
- **Exposure controls:**
- **Personal protective equipment**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing and wash before reuse.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes and skin.
- **Breathing equipment:** Not required.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves:**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material:**  
The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.
- **Eye protection:**



Tightly sealed goggles

- **Limitation and supervision of exposure into the environment:** None

## \* 9 Physical and Chemical Properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
  - **Form:** Paste
  - **Color:** White to off white
  - **Odor:** Odorless
  - **Odor threshold:** Not determined.
  - **pH-value:** Not applicable.
- **Change in condition**
  - **Melting point/Melting range:** Not determined.
  - **Flash point:** None
  - **Flammability (solid, gaseous):** Not determined.
  - **Ignition temperature:**  $\geq 427$  °C ( $\geq 800.6$  °F)
  - **Decomposition temperature:** Not determined.

(Contd. on page 6)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/29/2022

Reviewed on 09/29/2022

### Trade Name: Crawford's Vinyl Spackling Paste

- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Product does not present an explosion hazard.
- **Explosion limits:**
  - Lower:** 0 Vol %
  - Upper:** 13.4 Vol %
- **Vapor pressure @ 20 °C (68 °F):** ≤111 hPa (≤83.3 mm Hg)
- **Density @ 20 °C (68 °F):** 2.1978 g/cm<sup>3</sup> (18.3406 lbs/gal)
- **Relative density:** Not determined.
- **Vapor density:** Not applicable.
- **Evaporation rate:** Not applicable.
- **Solubility in / Miscibility with:**
  - Water:** Insoluble.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic:** Not applicable.
  - Kinematic:** Not applicable.
- **Solvent content:**
  - Organic solvents:** 17.9 %
  - VOC content:** 17.75 %
- **Other information:** No further relevant information available.

### 10 Stability and Reactivity

- **Reactivity:** No further relevant information available.
- **Chemical stability:** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological Information

- **Information on toxicological effects:**
- **Acute toxicity:**

#### · LD/LC50 values that are relevant for classification:

|                     |             |   |
|---------------------|-------------|---|
| <b>Trade Secret</b> |             |   |
|                     | LC50/48 hrs | 0.067 mg/l (Trout)<br>0.04 mg/l (Daphnia) |
| <b>Trade Secret</b> |             |   |
| Oral                | LD50        | >6,800 mg/kg (Rat)                        |
| Dermal              | LD50        | >3,400 mg/kg (rab)                        |
| Inhalative          | LC50/4 h    | >10.2 mg/l (Rat)                          |
| <b>Trade Secret</b> |             |   |
| Oral                | LD50        | 1,020 mg/kg (Rat)                         |

(Contd. on page 7)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/29/2022

Reviewed on 09/29/2022

### Trade Name: Crawford's Vinyl Spackling Paste

|            |          |                          |
|------------|----------|--------------------------|
| Inhalative | LC50/4 h | 0.8 mg/l (Trout) (96 hr) |
|------------|----------|--------------------------|

- **Primary irritant effect:**

- **On the skin:**

Irritant to skin and mucous membranes.

May cause an allergic skin reaction.

- **On the eye:** Irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

Carcinogenic

The product can cause inheritable damage.

- **Carcinogenic categories:**

- **IARC (International Agency for Research on Cancer):**

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

|              |    |
|--------------|----|
| Trade Secret | 3  |
| Trade Secret | 3  |
| Trade Secret | 3  |
| Trade Secret | 2B |

- **NTP (National Toxicology Program):**

Trade Secret

R

- **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

### 12 Ecological Information

- **Toxicity:**

- **Aquatic toxicity:**

Trade Secret

EC50 4.4 mg/l (Daphnia) (48 hr)

- **Persistence and degradability:** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential:** No further relevant information available.

- **Mobility in soil:** No further relevant information available.

- **Additional ecological information:**

- **General notes:** Generally not hazardous for water.

- **Results of PBT and vPvB assessment:**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects:** No further relevant information available.

(Contd. on page 8)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/29/2022

Reviewed on 09/29/2022

**Trade Name: Crawford's Vinyl Spackling Paste**

### 13 Disposal Considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household waste. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.
- **Uncleaned packaging**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport Information

- **UN-Number:**
- **DOT, ADR/ADN, ADN, IMDG, IATA** Non-Regulated Material
- **UN proper shipping name:**
- **DOT, ADR/ADN, ADN, IMDG, IATA** Non-Regulated Material
- **Transport hazard class(es):**
- **DOT, ADR/ADN, ADN, IMDG, IATA**
- **Class:** Non-Regulated Material
- **Packing group:**
- **DOT, ADR/ADN, IMDG, IATA** Non-Regulated Material
- **Environmental hazards:** Not applicable.
- **Special precautions for user:** Not applicable.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.
- **UN "Model Regulation":** Non-Regulated Material

### \* 15 Regulatory Information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

Trade Secret

Trade Secret

Trade Secret

· **TSCA (Toxic Substances Control Act):**

|            |   |        |
|------------|---|--------|
| 9004-62-0  | Hydroxyethyl Cellulose                  | ACTIVE |
| 25265-71-8 | Dipropylene glycol (isomer unspecified) | ACTIVE |
| 56-81-5    | Glycerol                                | ACTIVE |
| 1310-73-2  | Sodium Hydroxide                        | ACTIVE |

· **Hazardous Air Pollutants**

None of the ingredients are listed.

· **California Proposition 65:**



WARNING: This product can expose you to chemicals including the listed chemicals which are known to the State of California to cause cancer, birth defects and/or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/29/2022

Reviewed on 09/29/2022

### Trade Name: Crawford's Vinyl Spackling Paste

|  |   |        |
|--|---|--------|
| · <b>Chemicals known to cause cancer:</b>                                  |   |        |
| Trade Secret   |   |        |
| · <b>Chemicals known to cause reproductive toxicity for females:</b>       |   |        |
| None of the ingredients are listed.  |   |        |
| · <b>Chemicals known to cause reproductive toxicity for males:</b>         |   |        |
| None of the ingredients are listed.  |   |        |
| · <b>Chemicals known to cause developmental toxicity:</b>                  |   |        |
| None of the ingredients are listed.  |   |        |
| · <b>New Jersey Right-to-Know List:</b>                                    |   |        |
| 56-81-5  | Glycerol                                |        |
| 1310-73-2  | Sodium Hydroxide                        |        |
| · <b>New Jersey Special Hazardous Substance List:</b>                      |   |        |
| 1310-73-2  | Sodium Hydroxide                        | CO, R1 |
| · <b>Pennsylvania Right-to-Know List:</b>                                  |   |        |
| 25265-71-8   | Dipropylene glycol (isomer unspecified) |        |
| 56-81-5  | Glycerol                                |        |
| 1310-73-2  | Sodium Hydroxide                        |        |
| · <b>Pennsylvania Special Hazardous Substance List:</b>                    |   |        |
| 1310-73-2  | Sodium Hydroxide                        | E      |
| · <b>Carcinogenic categories:</b>  |   |        |
| · <b>EPA (Environmental Protection Agency):</b>                            |   |        |
| Trade Secret   |   | I      |
| Trade Secret   |   | D, CBD |
| · <b>TLV (Threshold Limit Value established by ACGIH):</b>                 |   |        |
| Trade Secret   |   | A3     |
| Trade Secret   |   | A4     |
| · <b>NIOSH-Ca (National Institute for Occupational Safety and Health):</b> |   |        |
| None of the ingredients are listed.  |   |        |

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms:**



· **Signal word:** Danger

· **Hazard-determining components of labeling:**

Trade Secret

· **Hazard statements:**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H340 May cause genetic defects.

H350 May cause cancer.

(Contd. on page 10)

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/29/2022

Reviewed on 09/29/2022

**Trade Name: Crawford's Vinyl Spackling Paste**

H335 May cause respiratory irritation.

**Precautionary statements:**

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302+P352 If on skin: Wash with plenty of water.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P312 Call a poison center/doctor if you feel unwell.
- P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**National regulations:**

The product is not subject to be labelled according with the prevailing version of the regulations on hazardous substances.

**Information about limitation of use:**

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other Information**

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

**Contact:****Abbreviations and acronyms:**

- ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- NIOSH: National Institute for Occupational Safety and Health
- OSHA: Occupational Safety & Health Administration

(Contd. on page 11)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) revised in 2012 and GHS Rev 03.

Issue date 09/29/2022

Reviewed on 09/29/2022

### Trade Name: Crawford's Vinyl Spackling Paste

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Acute Toxicity - Inhalation 3: Acute toxicity – Category 3

Acute Toxicity - Inhalation 4: Acute toxicity – Category 4

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Damage 1: Serious eye damage/eye irritation – Category 1

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation – Category 1

Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B

Carcinogenicity 1B: Carcinogenicity – Category 1B

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

Aspiration Hazard 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

· **\* Data compared to the previous version altered.**

SDS created by MSDS Authoring Services [www.msdsauthoring.com](http://www.msdsauthoring.com) +1-877-204-9106